



Yuasa Technisches Datenblatt

Yuasa YBX3205 - YBX3000 SMF Batterien

Leistung

Spannung	12V
Kapazität 20 Std (vorgegeben)	60Ah
Kaltstartstrom (A) EN1	540A

Abmessungen

Länge	230mm
Breite	174mm
Höhe	205mm

Maße und Gewichte

Durchschnittliches Gewicht inkl. Säure	14.9kg
--	--------



Gehäuseeigenschaften

Gehäusotyp	D23LS KOREA/BCI 86
Batteriehälter	B1
Ladezustandsanzeige	✓
Tragegriffe	✓
Entgasung	✓
Deckeltyp	SMF doppelwandige Deckelkonstruktion

Technologie

Flammschutz	✓
Technologie	Ca/Ca
Adskiller	PE
VDA Überschlagentest	✓
Empfohlener Ladestrom	4A
Performance Marking	W4-C2-V3-E1


Anschlusspol Typ

T1


Standard DIN Post



Zellenanordnung



Batteriehälter



Datenblatt erstellt am 16/09/2024 - E&EO



Yuasa Technical Data Sheet

Yuasa YBX3205 - YBX3000 SMF Batteries

Performance

Voltage	12V
Capacity (20-hour)	60Ah
Cold Cranking Amps (EN1)	540A

Dimensions

Length	230mm
Width	174mm
Height	205mm

Weights & Measures

Mean Weight with Acid	14.9kg
-----------------------	--------



Container Features

Case Type	D23LS KOREA/BCI 86
Hold Down	B1
State of Charge Indicator	✓
Handles	✓
End Venting	✓
Lid Type	SMF Double Lid

Technology

Flame Arrestor	✓
Technology	Ca/Ca
Separator	PE
VDA Roll Over Test	✓
Recommended Charge Rate	4A
Performance Marking	W4-C2-V3-E1


Terminal Type

T1


Standard DIN Post



Cell Assembly Layout



Battery Hold-down



Data Sheet generated on 16/09/2024 - E&OE