

YUASA


TAIWAN YUASA BATTERY CO.,LTD.

[Company](#) [Motorcycle](#) [Automobile](#) [VRLA](#) [Web Map](#) [Chinese](#)

Battery Type: RE7-12



- ☐ NLP
- ☐ NPH
- ☐ NPHW
- ☒ RE
- RE5-12
- RE7-12
- RE12-12
- ☐ REW
- ☐ REC
- ☐ Home



- | | |
|---|-----------------------------|
| 1. Nominal Voltage: | 12V |
| 2. Dimension | |
| Length: | 151±1 mm |
| Width: | 65±1 mm |
| Height: | 94±1 mm |
| Total Height: | 97.5±2 mm |
| Weight(Approx.) | 5.51Pounds(2.50kg) |
| 3. Nominal Capacity: | |
| 20hr rate of 0.35A TO 10.5V | 7.0AH |
| 3hr rate of 1.75A TO 10.02V | 5.25H |
| 1hr rate of 4.2A TO 9.6V | 4.2AH |
| Internal resistance: | 19mΩ~25mΩ |
| 6. MAX charged current: | 0.25CA (1.75A) |
| MAX discharged current: | 105A(5 sec) |
| 7. Operation temperature range | |
| Charge | 5℉ TO 104℉(-15℃ TO 40℃) |
| Discharge | 5℉ TO 122℉(-15℃ TO 50℃) |
| 8. Storage temperature range | 5℉ TO 104℉(-15℃ TO 40℃) |
| 9. Floating charge: | 13.65±0.15V |
| 10. Expected life(25℃) | 3~5 years in float charging |
| 11. Sealed construction | |
| Can be operated, charged or stored in any position without leakage. | |
| Can not be charged while the terminal is downward. | |
| 12. Standard terminal: | Faston Tab 187/250 |
| 13. Housing material: | ABS(FR) |

[Top](#) | [Go back](#) | [Home](#)

TAIWAN YUASA BATTERY CO.,LTD

NO.11,LANE227 FUYING RD.,HSIN CHUANG CITY.

TAIPEI HSIEN, TAIWAN, R.O.C.

TEL:886-2-29018261~4 FAX:886-229039626

Email: yua113@yuasa.com.tw