



VISION Rechargeable Products
Sealed Lead Acid Battery

www.vision-batt.com

HP&HF Series

High Rate Discharge

The new VISION HP/HF series batteries are specially designed for applications where need high power output. By optimum design of battery grids and platepaste formula, the HP/HF series can deliver up to 40% more power than VISION standard CP/FM series.

Shenzhen Center power tech co., ltd has more than 15 year's experience in the manufacturing of VRLA batteries. SZCPT is one of the biggest manufacturers of SLA (or VRLA) batteries in the world, the biggest one in Mainland China and the first in China to develop and commercialize the sealed lead-acid battery with brand name VISION and has been at the forefront of battery technology from day one.

SZCPT leads the world in innovative battery technology. Our global network of sales and service engineers, backed in turn by our agents and distributors, means that we are currently active in more than 100 countries.

Shenzhen Center Power Tech. Co., Ltd

HF12-470W-X 12V 100Ah

(Edition Jan 2014)

General Features

- Positive and negative plates in lead-calcium tinalloy
- Superior energy density
- Operates at a low internal pressure.
- Gas Recombination
- Usable in any orientation
- A recognized component of UL
- Very high power output
- Application specific designs
- A couple Range from 13W to 1010W per cell for 10' @ 1.60Vpc
- Six months shelf life at 20°C
- Design life 10 years



Dimensions and Weight

	SI Units	English Units
Length	330mm	13.0inch
Width	171mm	6.73inch
Height	215mm	8.46inch
Total Height	220mm	8.66inch
Approx. Weight	33.0Kg	72.8lbs

Performance Characteristics

- Nominal Voltage 12V
- Number of cell 6
- Nominal Capacity 77°F(25°C)
 - 10 min wattage @ 1.6V 470W/cell
 - 20 hour rate (5.25A, 10.5V) 105Ah
- Nominal Capacity 77°F(25°C)
 - 10 hour rate (10.0A, 10.8V) 100Ah
- Internal Resistance
 - Fully Charged battery 77°F(25°C) ≤ 4.0mOhms
- Self-Discharge
 - 3% of capacity declined per month at 20°C(average)
- Operating Temperature Range
 - Discharge -20~60°C
 - Charge -10~60°C
 - Storage -20~60°C
- Max. Discharge Current 77°F(25°C) 900A(5s)
- Charge Methods: Constant Voltage Charge 77°F(25°C)
 - Cycle use 2.40-2.45VPC
 - Maximum charging current 30A
 - Temperature compensation -30mV/°C
- Standby use 2.20-2.30VPC
 - Temperature compensation -20mV/°C



Center Power Industrial Park, Tongfu Industrial District Dapeng Town, 518120 Shenzhen, China
Tel: 86 755 84318088 Fax: 86 755 84318038 E-mail: sales@vision-batt.com
Website: <http://www.vision-batt.com>

HF12-470W-X 12V 100Ah

Discharge Data

Constant Current Discharge Data (Amperes at 25°C)											
End Voltage Per cell / V	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	271	222	180	155	138	123	111	101	92.2	84.8	78.7
1.65	256	211	171	147	131	116	105	96.2	87.8	80.8	75.1
1.70	242	199	162	139	124	110	100	91.3	83.4	76.9	71.4
1.75	227	188	152	131	117	104	94.1	86.4	79.0	72.9	67.8
1.80	218	181	148	127	114	101	91.8	84.3	77.1	71.2	66.3

Constant Power Discharge Data (Watts per cell at 25°C)											
End Voltage Per cell / V	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	470	378	310	270	243	216	196	180	164	151	140
1.65	453	364	300	261	235	209	190	175	159	147	136
1.70	435	351	289	252	227	202	184	169	154	143	133
1.75	418	338	279	243	219	195	177	164	150	138	129
1.80	400	325	268	234	211	188	171	158	145	134	125

(Note)The above characteristics data are average values obtained within three charge/discharge cycles not the minimum values. All data shall be changed without notice, Vision reserves the right to explain and update the information contained hereinto.

Performance drawings

